HORIZONTAL SELF-CONTAINED AIR CONDITIONERS

These SR-series self-contained air conditioners (horizontal) are designed for commercial (i.e. supermarket, theatres, restaurants, office building) and industrial application.

FEATURES

- Heavily zinc coated galvanized steel cabinet.
- Various static pressure.
- Motor with a set of variable pitch diameter pulleys.
- Blower motors are fitted with inherent thermal protectors.
- Hermetic sealed scroll compressors.
- Permanent split capacitor condenser fan motor.
- High and low pressure switch.
- Filter drier.
- Factory test run and fully charged with R22 or R410a.
- Pre Filter.

OPTIONAL COMPONENTS

- Room thermostat.
- Under and over voltage protection.
- Heat pump.
- Electric heater.
- R407c.
- Medium Filter.
- Bag Filter.



SR

SPECIFICATIONS

MODEL	COOLING CAPACITY				AIR FLOW RATE		DIMENSIONS (mm)			NET WEIGHT (kg)
	R22		R410A							
	Btu/h	kW	Btu/h	kW	CFM	L/S	Height	Width	Depth	
SR052Z	51,000	14.9	49,800	14.6	1,631	770	785	1,020	1,470	180
SR060Z	61,000	17.88	59,300	17.4	1,801	850	785	1,020	1,470	190
SR077X	77,000	22.5	77,000	22.7	2,436	1,150	1,300	1,100	1,800	300
SR104X	102,000	29.8	100,000	29.4	3,178	1,500	1,300	1,100	1800	320
SR122X	122,000	35.7	127,000	37.3	3,877	1,830	1,400	1,400	2,450	530
SR154X	149,000	43.6	153,000	44.8	4,597	2,170	1,400	1,400	2,450	570
SR208X	206,000	60.3	201,000	58.8	6,356	3,000	1,604	1,890	2,600	960
SR244X	242,000	71	254,000	74.3	7,754	3,660	2,046	1,890	3,000	970
SR307X	299,000	87.6	306,000	89.7	9,174	4,330	2,046	1,890	3,000	1,080
SR360X	351,000	103	342,000	100.2	11,059	5,220	2,046	1,890	3,000	1,090
SR440X	440,000	129	435,000	127.4	13,347	6,300	2,100	2,040	4,000	1,700
SR550X	503,000	147.4	489,000	143.4	15,890	7,500	2,100	2,040	4,000	2,000
SR600X	676,000	198.1	662,000	193.9	20,000	9,440	2,500	2,100	4,300	2,640